imageRUNNER 2425 II

Canon
Delighting You Always

Effortless Productivity, *Elevated*

Packing advanced monochrome printing features in a compact form factor, the new imageRUNNER 2425 II boasts a range of updated operability and security features, optimising print processes for a wide range of businesses.





INTUITIVE USABILITY

The 17.7 cm (7-inch) colour touch panel provides greater visibility at a glance with smooth operability. Possibility for customizable screen layouts, shortcut button creation, and personalized settings — empowering users to work faster and more efficiently.

MORE WAYS TO CONNECT

Boost productivity with a suite of connectivity features designed to make sharing files easy.

- uniFLOW Online
- AirPrint and Mopria mobile connectivity
- Dedicated USB port

ROBUST SECURITY

Includes multiple authentication methods to prevent unauthorised access, and Verify System at Start-up to ensure firmware and application integrity from the moment the machine powers on.

Business Can Be Simple

SPECIFICATIONS

MAIN UNIT	imageRUNNER 2425 II
Machine Type	A3 Monochrome Laser Multifunctional
Core Functions	Print, Copy, Scan, Send and Optional Fax
Control Panel	17.7 cm (7-inch) TFT LCD WVGA Colour touch panel
Memory	3.0 GB RAM
Storage	30 GB
Interface Connection	NETWORK 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n)
	OTHERS USB 2.0 (Host) x3, USB 2.0 (Device) x1
Paper Supply Capacity (A4, 80gsm)	Standard: 350 sheets
	Maximum: 600 sheets (with Cassette Feeding Module-AM1)
Paper Output Capacity (A4, 80gsm)	250 sheets
Supported Media Sizes	Multi-Purpose Tray: A3, A4, A4R, A5, A5R, B4, B5, B5R, Envelope (COM10, Monarch, DL, ISO-C5) Custom size/Free size: 95.0 x 139.7 mm to 297.0 x 431.8 mm
	Paper Cassette: Standard size: A3, A4, A4R, A5R, B4, B5, B5R
Supported Media Weights	Multi-Purpose Tray: 60 to 157 g/m2 (gsm)
	Paper Cassette: 64 to 90 g/m2 (gsm)
	Duplex: 60 to 90 g/m2 (gsm)
Warm-up Time	4 s or less* *Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display.*
	12 s or less* *Time from device power on, until copy ready (not print reservation)*
	From Sleep Mode: 10 s or less
Dimensions (W x D x H)	627 x 665 x 522 mm (with Platen cover)
Installation Space (W x D)	1,065 x 1,285 mm
Weight* *Including platen cover and regular toner*	Approx. 35.2kg
PRINT	
Print Speed	**1 sided:** Up to 25 pages/min (A4), Up to 12 pages/min (A3), Up to 11 pages/min(A4R)
Print Resolution (dpi)	600 x 600
Page Description Languages	Standard: UFR II, Optional: PCL6/PCL5, Adobe PostScript 3
Direct Print	Supported file types: PDF, EPS, TIFF/JPEG, and XPS
Fonts	PS fonts: 136 Roman PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T*1 (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts*2 *1 Optional PCL International Font Set-A1 is required.* *2 Optional Barcode Printing Kit-D1 is required.*
Operating System	UFRII: Windows®10/11/Server2016/Server2019/Server2022/ Server2025,macOS® (10.14 or later) PCL: Windows®10/11/Server2016/Server2019/Server2022/ Server2025 PS: Windows®10/11/Server2016/Server2019/Server2022/ Server2025, macOS® (10.14 or later) PPD:Windows®10/11, macOS® (10.15 or later) *As of Dec 2024*
COPY	
Copy Speed	**1-sided:** Up to 25 pages/min (A4), Up to 12 pages/min (A3), Up to 11 pages/min (A4R)
First-Copy-Out Time (A4)	Platen: Approx. 7.4 s or less
Copy Resolution (dpi)	600 x 600
Multiple Copies	Up to 9,999 copies
Copy Density	Automatic or Manual (9 Levels)
Magnification	Variable zoom: 25% to 400% (1% Increments)
SCAN	
Type	Standard: Platen Cover
	Optional: Single-pass Duplexing Automatic Document Feeder
Document Feeder Paper Capacity (80 gsm)	Up to 100 Sheets

SCAN	imageRUNNER 2425 II
Scan Resolution (dpi)	600 x 600
Acceptable Paper Weight	Document Feeder sheet media weight: 1-sided Scanning: 38 to 220 g/m2 (gsm) (BW/CL) 2-sided Scanning: 50 to 220 g/m2 (gsm) (BW/CL) Only 1-sheet feeding is supported for paper with 38-42 g/m2 (gsm)
Supported Media Sizes	Platen: 297.0 x 431.8 mm
	Document Feeder: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom size: 48.0 x 85.0 mm to 304.8 x 431.8 mm
Document Feeder Scan Speed (ipm: BW/CL; A4)	1-sided Scanning: 35/35 (300 dpi, send), 30/30 (600 dpi, copy) 2-sided Scanning: 70/70 (300 dpi, send), 60/40 (600 dpi, copy)
Pull Scan Specifications	Color Network ScanGear2 for both TWAIN and WIA
	Supported OS: Windows® 10/11/Server 2016/Server 2019/ Server 2022/Server 2025 *As of Dec 2024*
Scan Method	Push scan, Pull scan, Scan to Network, Scan to USB Memory Key, Scan to Mobile devices, Scan to cloud (uniFLOW Online*) *Optional*
SEND	
Destination	Standard: E-mail/Internet FAX (SMTP*), SMB, FTP, WebDAV, Mail Box *Available OAuth 2.0 authentication method on Microsoft 365 and Google Workspace*
	Optional: Super G3 FAX, IP Fax
Address Book	LDAP (2,000)/Local (1,600)/One-touch (200)
Communication Protocol	File: FTP (TCP/IP), SMB 3.1.1 (TCP/IP), WebDAV
	Email/iFax: SMTP (Send), POP3 (Receive)
File Format	Standard: TIFF (MMR), JPEG*, PDF (Compact, Searchable, Optimize for Web, PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word) *Single page only*
FAX	
Maximum Number of Connection Lines	1
Modem Speed	Super G3: 33.6 kbps
	G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution (dpi)	400 x 400 (Ultrafine), 200 x 400 (Super Fine), 200 x 200 (Fine), 200 x 100 (Normal)
Sending Size	Sending: A3, A4, A4R, A5*2, A5R*2,B4, B5*1, B5R*2 *1 Send as B4 short* *2 Send as A4*
Receiving Size	A3, A4, A4R, A5, A5R, B4, B5, B5R
FAX Memory	Up to 30,000 pages (2,000 jobs)
Speed Dials	Max. 200
Group Dials/Destinations	Max. 199 dials
Sequential Broadcast	Max. 256 addresses
Memory Backup	Yes
ENVIRONMENTAL SPECIFICATIONS	
Power Source	220-240V 50/60Hz 2.8A
Power Consumption	Maximum: Approx. 1,500 W
	Standby: Approx. 27.0 W*1 *1 Reference value: measured one unit*
	Sleep mode: Approx. 0.9 W*2 *2 Wireless LAN power serve mode OFF* *2 Sleep mode is not available in all circumstances due to certain settings.*
PAPER SUPPLY OPTIONS	
Cassette Feeding Module-AM1	Paper Capacity: 250 sheets (80 g/m2 (gsm)) Paper Type: Plain, Recycled, Colour, Pre-punched Paper Size: A3, A4, A4R, A5, B4, B5, B5R Paper Weight: 64 to 90 gsm Power Source: From the Main Unit

Canon
Delighting You Always

CANON INDIA PVT. LTD.
7th Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase 111, Gurugram-122002
Ph.: 0124-4160000 I Fax: 0124-4160011 I Web: in.canon

DEALER'S STAMP

This document is for information purposes only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.

© Canon Singapore Pte Ltd 2026. All rights reserved.