imageRUNNER
C3326

Canon
Delighting You Always

# ELEVATING WORKSPACE PERFORMANCE

## Functional and Efficient




Touch Panel

Print/Copy/ Scan/fax

Mobile Support

Wi-Fi Connectivity

Optimal Security

**Business Can** Be Simple




# ENHANCING WORKSPACES




## EASE OF ACCESSIBILITY

Tap into a rich variety of functions through the built-in 177.8 mm (7 in) operation panel, which is fully customisable to accomodate for organisation of commonly used processes. The Timeline feature displays past job histories which can be conveniently re-executed at a touch, making processes easy for users who repeatedly utilise the same functions and settings.




## EFFICIENT DOCUMENT SCANNING

Ensure optimal readability and orientation of scanned documents with the Scan Preview function. Simply review scanned items on the display to rectify any scanning errors before sending, saving time and providing added convenience.

# EFFORTLESS DOCUMENT HANDLING

The new multi-functional device offers various finishing options to further ease workflow. Select from ECO-staple, Staple-On-Demand and hole-punching functions that reduces the need for manual collating and stapling.



**8 SHEETS**

### ECO-STAPLE

Up to 8 sheets (A4/80g/m² (gsm)

**50 SHEETS**

### STAPLE-ON-DEMAND

Up to 50 sheets (A4/80g/m² (gsm)



# SECURE DATA PROTECTION

Worry less about data being compromised using advanced and up-to-date security features in the imageRUNNER C3326. Keep documents safe with authentication and encryption.

## Securing Document Access

Manage important or confidential documents securely to prevent leakage of information. The Force Hold Print feature holds the documents at the device and releases it only upon authentication, preventing accidental or unwanted access.

Encrypted PDF to prevent leakage of information

## Preventing Risks

Scanned documents in formats like PDF or XPS can be encrypted to secure their digital data with an additional layer of protection alongside limiting access only to the right document handler.

User authentication features to manage access

## uniFLOW Online/ Online Express

The imageRUNNER C3326 offers login authentication with uniFLOW Online Express, providing additional document security functions while granting access only to permissible users.

uniFLOW online express



# Specifications

| MAIN UNIT | |
|---|---|
| **Machine Type** | A3 Colour Laser Multifunctional |
| **Core Functions** | Print, Copy, Scan, Send and Optional Fax |
| **Control Panel** | 177.8 mm (7in) TFT LCD WVGA Colour Touch panel |
| **Memory** | Standard: 2.0GB RAM |
| **Storage** | Standard: 64GB eMMC (available space 30GB)<br>Optional: 256GB SSD |
| **Interface Connection** | Network<br>Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n) |
| | Others<br>Standard: USB 2.0 (Host) x2, USB 2.0 (Device) x1 |
| **Paper Supply Capacity (A4, 80g/m² (gsm)** | Standard: 1 200 sheets<br>(100 sheets Multi-purpose tray, 2 x 550 sheets paper cassette)<br>Maximum: 2 300 sheets (with Cassette Feeding Unit-AW1) |
| **Paper Output Capacity (A4, 80g/m² (gsm)** | Standard: 250 sheets<br>Maximum: 645 sheets (with Inner Finisher-L1 and Copy Tray-T2) |
| **Supported Media Types** | Multi-purpose tray:<br>Thin, Plain, Heavy, Recycled, Coated[1], Colour, Tracing, Bond, Transparency, Labels, Pre-punched, Letterhead, Envelope, Postcard<br>[1]SRA3 is unsupported for Coated (257 to 300g/m² (gsm) |
| | Upper Cassette:<br>Thin, Plain, Heavy, Recycled, Colour, Bond, Transparency, Pre-punched, Letterhead, Envelope[1], Postcard<br>[1]Envelope Feeder Attachment Kit B (standard) is required except ISO-C5. |
| | Lower Cassette:<br>Thin, Plain, Heavy, Recycled, Colour, Bond, Transparency, Pre-punched, Letterhead, Envelope[1], Postcard<br>[1]Envelope Feeder Attachment Kit A (standard) is required. |
| **Supported Media Sizes** | Multi-purpose tray:<br>Standard size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R<br>Custom size: 98.4 x 139.7 mm to 320.0 x 457.2 mm<br>Free size: 100.0 x 148.0 mm to 304.8 x 457.2 mm<br>Envelopes: COM10 No.10, Monarch, ISO-C5, DL<br>Envelope custom size: 98.0 x 98.0 mm to 320.0 x 457.2 mm |
| | Upper Cassette:<br>Standard size: A4, A5, A5R, A6R, B5<br>Custom Size: 105.0 x 148.0 mm to 297.0 x 215.9 mm<br>Envelopes: ISO-C5 |
| | Lower Cassette:<br>Standard size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R<br>Custom Size: 105.0 x 148.0 mm to 304.8 x 457.2 mm<br>Envelopes[1]: COM10 No.10, Monarch, DL<br>[1]Envelope Attachment A (standard) is required. |
| **Supported Media Weights** | Multi-purpose tray: 52 to 300g/m² (gsm)[1]<br>[1]SRA3 is unsupported for Coated (257 to 300g/m² (gsm).<br>Paper weight supported with Media Adjustment Kit-A1: 60 to 300g/m² (gsm). |
| | Upper/Lower Cassette: 52 to 256g/m² (gsm) |
| | Duplex: 52 to 220g/m² (gsm) |
| **Warm-up Time (Quick start mode: ON)** | 4 s or Less[1]<br>[1]Time from device power on to when copy icon appears and is enabled to operate on the touch panel display. |
| | From Sleep Mode: 10 s or less |
| | From Power On: 10 s or less[1]<br>[1]Time from device power-on, until copy ready (not print reservation) |
| **Dimensions (W x D x H)** | With Platen Cover-Y3: 565.0 x 659.0 x 788.0 mm<br>With DADF-BA1: 565.0 x 687.0 x 891.0 mm |
| **Installation Space (W x D)** | Basic:<br>978 x 1 088 mm (with Platen Cover-Y3 + right door & multi-purpose tray opened + paper cassette opened)<br>Fully Configured:<br>1 286 x 1 116 mm (with DADF-BA1 + Inner Finisher-L1 + Copy Tray-T2 extended + paper cassette opened) |
| **Weight (Including toner)** | With Platen Cover-Y3: Approx. 71 kg<br>With DADF-BA1: Approx. 78 kg |

| PRINT SPECIFICATIONS | |
|---|---|
| **Print Speed (BW)** | 1-sided: Up to 26 pages/min (A4), Up to 15 pages/min (A3), Up to 20 pages/min (A4R) |
| **Print Resolution (dpi)** | 600 × 600,<br>1 200 x 1 200 (half-speed) |
| **Page Description Languages** | Standard: UFR II<br>Option: Adobe PostScript 3, PCL6 |
| **Direct Print (RUI)** | PDF, EPS, TIFF/JPEG and XPS |
| **Printing from Mobile and Cloud Applications** | AirPrint, Mopria, Canon PRINT Business, uniFLOW Online and Universal Print |
| **Fonts** | PS fonts: 136 Roman<br>PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T[1] (Japanese, Korean, Simplified and Traditional Chinese) , Barcode fonts[2]<br>[1]Optional PCL International Font Set-A1 is required.<br>[2]Optional Barcode Printing Kit-D1 is required. |
| **Operating System** | UFR II: Windows® 10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022, macOS(10.13 or later)<br>PCL: Windows® 10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022<br>PS: Windows® 10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022, macOS(10.13 or later)<br>PPD: Windows® 10/11, macOS(10.13 or later) |

| COPY SPECIFICATIONS | |
|---|---|
| **Copy Speed (BW/CL)** | 1-sided: Up to 26 pages/min (A4), Up to 15 pages/min (A3), Up to 20 pages/min (A4R) |
| **First-Copy-Out Time (A4, BW/CL)** | Approx. 7.0/8.7 s or less |
| **Copy Resolution (dpi)** | 600 x 600 |
| **Multiple Copies** | Up to 999 copies |
| **Copy Density** | Automatic or Manual (9 Levels) |
| **Magnification** | Variable zoom: 25% to 400% (1% Increments)<br>Preset reduction/enlargement: 25%, 50%, 61%, 70%, 81%, 86%, 100%(1:1), 115%, 122%, 141%, 200%, 400% |

| SCAN SPECIFICATIONS | |
|---|---|
| **Type** | Option: Platen Cover-Y3 or DADF-BA1(2-sided to 2-sided) |
| **Document Feeder Paper Capacity (80 gsm)** | Up to 100 sheets |
| **Acceptable Originals and Weights** | Platen: Sheet, Book and 3-Dimensional objects |
| | Document Feeder media weight:<br>1-sided scanning: 38 to 128g/m² (gsm) (BW), 64 to 128g/m² (gsm) (CL)<br>2-sided scanning: 50 to 128g/m² (gsm) (BW), 64 to 128g/m² (gsm) (CL) |
| **Supported Media Sizes** | Platen: Max. scanning size: 297.0 x 431.8 mm |
| | Document Feeder media size:<br>A3, A4, A4R, A5, A5R, B4, B5, B5R, B6<br>Custom size: 128.0 x 139.7 mm to 297.0 x 431.8 mm |
| **Scan Speed (ipm: BW/CL; A4)** | DADF-BA1:<br>1-sided Scanning: 70/70 (300 x 300 dpi, send), 51/42 (600 x 600 dpi, copy)<br>2-sided Scanning: 35/35 (300 x 300 dpi, send), 25.5/25.5 (600 x 600 dpi, copy) |
| **Scan Resolution (dpi)** | Scan for Copy: 600 x 600<br>Scan for Send: (Push) 600 x 600 (SMB/FTP/WebDAV/IFAX), (Pull) 600 x 600<br>Scan for Fax: 600 x 600 |
| **Pull Scan Specifications** | Color Network ScanGear2. For both TWAIN and WIA |
| **Supported OS** | Supported OS: Windows® 10/11/Server2012/Server2012 R2/Server2016/Server 2019/Server2022 |

| SEND SPECIFICATIONS | |
|---|---|
| **Destination** | Standard: E-mail/Internet FAX (SMTP), SMB, FTP, WebDAV<br>Optional: Super G3 FAX |
| **Address Book** | LDAP (2 000)/Local (1 600)/One-touch (200) |
| **Send Resolution (dpi)** | Push: (CL) up to 300 x 300/(BW) up to 600 x 600<br>Pull: (CL) up to 300 x 300/(BW) up to 600 x 600 |
| **Communication Protocol** | FTP: (TCP/IP), SMB3.1.1(TCP/IP), WebDAV<br>Email/iFax: SMTP(send), POP3(receive) |
| **File Format** | Standard:<br>TIFF (MMR), JPEG[1], PDF (Compact, OCR (Text Searchable)), Optimise PDF for Web, Format to PDF/A-1b, Encrypt), XPS (Compact, OCR (Text Searchable)), PDF/XPS (Device Signature), Office Open XML (PowerPoint, Word)<br>Option:<br>PDF (Trace & Smooth), PDF/XPS (User Signature)<br>[1]Single-Page only. |

| FAX SPECIFICATIONS | |
|---|---|
| **Maximum Number of Connection Lines** | 1 |
| **Modem Speed** | Super G3: 33.6 kbps<br>G3:14.4 kbps |
| **Compression Method** | MH, MR, MMR, JBIG |
| **Resolution (dpi)** | 400 x 400 (Ultrafine), 200 x 400 (Superfine), 200 x 200 (Fine), 200 x 100 (Normal) |
| **Sending/Recording Size** | Sending: A3, A4, A4R, A5[1], A5R[1], B4, B5[2], B5R[1]<br>Receiving: A3, A4, A4R, A5, A5R, B4, B5, B5R<br>[1]Sent as A4<br>[2]Sent as B4 short |
| **FAX Memory** | Up to 30 000 pages (2 000 jobs) |
| **Speed Dials** | Max. 200 |
| **Group Dials/Destinations** | Max. 199 dials |
| **Sequential Broadcast** | Max. 256 addresses |
| **Memory Backup** | Yes |

| ENVIRONMENTAL SPECIFICATIONS | |
|---|---|
| **Operating Environment** | Temperature: 10 to 30 °C<br>Humidity: 20 to 80% RH (Relative Humidity) |
| **Power Source** | 220-240V, 50/60Hz, 5A |
| **Power Consumption** | Maximum: Approx. 1 500W<br>Sleep Mode: Approx. 0.8W[1]<br>[1]0.8W is not available in all circumstances due to certain settings. |

**OTHER ACCESSORIES**

DADF-BA1, Platen Cover-Y3, Cassette Feeding Unit-AW1, Inner 2Way Tray-M1, Copy Tray-T2, Inner Finisher-L1, Inner 2/3 Hole Puncher-D1, Inner 2/4 Hole Puncher-D1, IC Card Reader Attachment-B4, Option Attachment Kit For Reader-A2, Utility Tray-B1, Media Adjustment Kit-A1, PS Printer Kit-CS1E, PCL International Font Set-A1E, PCL Asian Font Set-A1E, Barcode Printing Kit-D1E, Universal Send Trace & Smooth PDF Kit-A1E, Universal Send Digital User Signature Kit-C1E, Super G3 Fax Board-BN1, Remote Fax Kit-A1, Optional Data Storage Kit-A1, Copy Control Interface Kit-D1, ADF Access Handle-A1, Staple-P1

Canon

Delighting You Always

**CANON INDIA PVT. LTD.**
7th Floor, Tower B, Building #5, DLF Epitome Building,
DLF Phase III, Gurugram-122002
Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.

© 2023 Canon India Pvt. Ltd. All rights reserved. Printed in India.